



ADFlex Gas EN16436

Tubo flessibile in PVC per mandata gas ideale per apparecchi domestici ed esterni secondo EN 16436. Omologazione soggetta a controllo DVGW.

Normativa di riferimento: EN16436-1

Diametri nominali:

Classe 2 (10bar) 4mm - 6,3mm - 8mm - 9mm

Classe 3 (30bar) 4mm - 6,3mm

ADFlex Gas EN16436

PVC hose for gas supply ideal for domestic and external appliances according to EN 16436. Approval subject to DVGW control.

Reference regulation: EN16436-1

Nominal diameters of:

Class 2 (10bar) 4mm - 6,3mm - 8mm - 9mm

Class 3 (30bar) 4mm - 6,3mm

| Codice | Ø (mm) | g/m | Materiali | | | P.E. (bar) | P.S. (bar) | T. Utilizzo (°C) | Min. Curva (mm) | EAN | |
|------------|-----------|-----|-----------|------|------|---------------|---------------|---------------------|-----------------------|-------|---------------|
| | | | Int. | Est. | Riga | | | | | | |
| ADGDE 0411 | 4x11 | 125 | ● | ● | / | 10 Bar | 30 Bar | -30°/+70° | - | 50 m | 8019071004987 |
| | | | | | | | | | | 100 m | 8019071004994 |
| ADGDE 0613 | 6,3x13,3 | 160 | ● | ● | / | 10 Bar | 30 Bar | -30°/+70° | - | 50 m | 8019071005007 |
| | | | | | | | | | | 100 m | 8019071005014 |
| ADGDE 0815 | 8x15 | 190 | ● | ● | / | 10 Bar | 30 Bar | -30°/+70° | - | 50 m | 8019071005021 |
| | | | | | | | | | | 100 m | 8019071005038 |
| ADGDE 0916 | 9x16 | 205 | ● | ● | / | 10 Bar | 30 Bar | -30°/+70° | - | 50 m | 8019071005045 |
| | | | | | | | | | | 100 m | 8019071005052 |
| ADGDE 0412 | 4x12 | 150 | ● | ● | / | 30 Bar | 90 Bar | -30°/+70° | - | 50 m | 8019071005076 |
| | | | | | | | | | | 100 m | 8019071005083 |
| ADGDE 0616 | 6,3x16,3 | 270 | ● | ● | / | 30 Bar | 90 Bar | -30°/+70° | - | 50 m | 8019071005090 |
| | | | | | | | | | | 100 m | 8019071005106 |