



ADFlex Air ML

Tubo doppio strato con rinforzo in Poliestere (PES). Idoneo ad uso intensivo per pressioni d'esercizio fino a 20bar/290psi. Prodotto con materiali conformi ai regolamenti RoHS e REACH.

Diametri interni: da 6mm a 32mm

Pressione d'esercizio: 20 bar (290 psi)

Fattore di Sicurezza: 3:1

Marchatura: ADFLEX AIR ML - DN(XX) - WP(XX)Bar -

MADE IN ITALY

Fattore di Sicurezza: 3:1

Marchatura: ADFLEX AIR ML - DN(XX)

- WP(XX)Bar -MADE IN ITALY

ADFlex Air ML

Double layer hose with Polyester reinforcement (PES). Suitable for intensive use for operating pressures up to 20bar/290psi. Produced with materials that comply with Rohs and REACH regulations.

Internal diameters: from 6mm to 32mm

Operating pressure: 20 bar (290 psi)

Safety factor: 3:1

Marking: ADFLEX AIR ML - DN(XX) - WP(XX)Bar - MADE IN ITALY

Mark: ADFLEX AIR ML - DN(XX)

- WP(XX)Bar - MADE IN ITALY

Codice	Ø	g/m	Materiali			P.E.	P.S.	T. Utilizzo	Min. Curva	EAN
			Int.	Est.	Riga					
	(mm)					(bar)	(bar)	(°C)	(mm)	EAN 50 m
ADAIR ML 0612	6x12	115	●	●	●	20	60	-20°/+60°	35	8019071003614
ADAIR ML 0814	8x14	140	●	●	●	20	60	-20°/+60°	32	8019071003669
ADAIR ML 0815	8x15	170	●	●	●	20	60	-20°/+60°	35	8019071003713
ADAIR ML 1017	10x17	200	●	●	●	20	60	-20°/+60°	40	8019071003768
ADAIR ML 1319	13x19	205	●	●	●	20	60	-20°/+60°	60	8019071003812
ADAIR ML 1624	16x24	340	●	●	●	20	60	-20°/+60°	65	8019071003867
ADAIR ML 1928	19x28	445	●	●	●	20	60	-20°/+60°	70	8019071003911
ADAIR ML 2535	25x35	630	●	●	●	20	60	-20°/+60°	90	8019071003966
ADAIR ML 3244	32x44	960	●	●	●	20	60	-20°/+60°	130	8019071004017