



## ADFlex Fuels

Tubo doppio strato con rinforzo in Poliestere (PES). Layer interno con miscela idonea al passaggio di carburanti non aromatici, gasolio, oli combustibili o altri derivati petroliferi.

**Diametri nominali: da 5mm a 25mm**  
**Pressione d'esercizio: max 10 bar (145 psi)**

## ADFlex Fuels

*Double layer tube with Polyester reinforcement (PES). Internal layer with compound suitable for the passage of non-aromatic fuels, diesel, fuel oils or other petroleum derivatives.*

**Nominal diameters: from 5mm to 25mm**  
**Operating pressure: max 10 bar (145 psi)**

Codice	Ø (mm)	g/m	Materiali			P.E. (bar)	P.S. (bar)	T. Utilizzo (°C)	Min. Curva (mm)	EAN EAN 50 m
			Int.	Est.	Riga					
ADFUELS 0511	05x10,5	95	●	●	●	5 Bar	15 Bar	-15°/+50°	35	8019071005373
ADFUELS 0612	06x12	115	●	●	●	5 Bar	15 Bar	-15°/+50°	35	8019071005397
ADFUELS 0814	08x14	140	●	●	●	5 Bar	15 Bar	-15°/+50°	40	8019071005410
ADFUELS 1016	10x16	170	●	●	●	5 Bar	15 Bar	-15°/+50°	50	8019071005434
ADFUELS 1926	19x26	335	●	●	●	5 Bar	15 Bar	-15°/+50°	95	8019071005458
ADFUELS 2533	25x33	495	●	●	●	5 Bar	15 Bar	-15°/+50°	110	8019071005472