



ADFlex TRECCIA 80 / 100

Tubo in PVC con doppio rinforzo in poliestere ad alta tenacità ideale per il passaggio di acqua, soluzioni fungicide, pesticidi e fertilizzanti, per irrorazione con pressione di esercizio fino a 80 bar/1160 psi. Disponibile nelle varianti a singolo e doppio rinforzo.

Diametri interni: da 8mm a 13mm

Pressione d'esercizio: 80 bar (1160 psi)

Fattore di Sicurezza: 3:1

Marchatura: ADFLEX TRECCIA 80 - Dn XX - WP 80Bar BP 240Bar - MADE IN ITALY

ADFlex TRECCIA 80 / 100

PVC hose with double reinforcement in high tenacity polyester ideal for water, fungicide solutions, pesticides and fertilizers and for spraying with operating pressure up to 80 bar / 1160 psi. Available in single and double reinforcement variants.

Internal diameters: from 8mm to 13mm

Operating pressure: 80 bar (1160 psi)

Safety factor: 3: 1

Marking: ADFLEX TRECCIA 80 - Dn XX - WP 80Bar BP 240Bar - MADE IN ITALY

Codice	Ø	g/m	Materiali		Tipo	P.E.	P.S.	T. Utilizzo	Min. Curva	EAN
			Int.	Est.						
	(mm)				S / D	(bar)	(bar)	(°C)	(mm)	EAN 50 m
ADTRX80 0815	08x15	160	●	●	S	80	240	-05°/+40°	40	8019071008190
ADTRX80 1018	10x18	220	●	●	S	80	240	-05°/+40°	50	8019071008206
ADTRX80 1322	13x22	310	●	●	S	80	240	-05°/+40°	60	8019071008213
ADTRX80D 0815	08x15	160	●	●	D	80	240	-10°/+50°	30	8019071008220
ADTRX80D 1018	10x17,5	210	●	●	D	80	240	-10°/+50°	40	8019071008237
ADTRX80D 1322	13x21,5	285	●	●	D	80	240	-10°/+50°	50	8019071008244
ADTRX100D 0816	08x16	185	●	●	D	100	300	-05°/+40°	40	8019071008251
ADTRX100D 1019	10x19	250	●	●	D	100	300	-05°/+40°	60	8019071008268
ADTRX100D 1324	13x24	380	●	●	D	100	300	-05°/+40°	80	8019071008275